



**CORE VAC
PARTS LIST**

**MODEL
CV1900AV**

OCTOBER 2021

Index

INTRODUCTION.....	PAGE 3
SAFETY & HAZARDOUS WARNING.....	PAGE 4
FILTER INFORMATION.....	PAGE 5
OPERATION & MAINTAINENCE.....	PAGE 6 - 11
VACUUM PARTS	
BODY GROUP.....	PAGE 12 -15
AIR GROUP.....	PAGE 16- 17
ELECTRIC GROUP.....	PAGE 18
ADDITIONAL SPARE PARTS.....	PAGE 19

INTRODUCTION

FORWARD

WARNING READ THIS MANUAL CAREFULLY PRIOR TO OPERATING THE EQUIPMENT IN ORDER TO UNDERSTAND HOW TO OPERATE AND SERVICE THE EQUIPMENT CORRECTLY. FAILURE TO PROPERLY REVIEW THIS MANUAL COULD RESULT IN PERSONAL INJURY OR EQUIPMENT DAMAGE.

This manual should be considered a permanent part of the equipment and should remain with the equipment at all times. Please note the following:

Measurements in this manual are given in metric and standard U.S. measurement equivalents.

Use only correct replacement parts and fasteners. Fasteners may require specific tools.

Right and left hand sides are determined by facing forward while sitting in the seat behind the steering wheel.

THIRD-PARTY MANUFACTURER INFORMATION

This equipment contains an engine manufactured by a third-party manufacturer. This engine may be covered by the manufacturer's standard factory warranty and the manufacturer may require that all repairs and/or service be completed pursuant to its warranty terms and conditions. Please refer to the product manual and Warranty Breakdown for additional information on this warranty and any registration requirements.

GENERAL SAFETY & HAZARDOUS MATERIALS WARNING

WARNING SURFAC PREPARATION EQUIPMENT CAN BE DANGEROUS IF NOT OPERATED PROPERLY. THE OPERATOR IS RESPONSIBLE FOR THE SAFE OPERATION OF THIS EQUIPMENT. The operator must carefully read and follow any warnings or safety instructions provided with the equipment prior to operating the equipment. Do not remove any safety devices or warnings on the equipment.

WARNING FLOOR AND/OR DECK SURFACES MAY BE COATED WITH OR CONTAMINATED BY HAZARDOUS MATERIALS. Typical examples of hazardous materials include (i) tile mastic (likely to contain *asbestos*); (ii) stained areas near electrical equipment (potentially containing *PCBS*); (iii) paint (potentially containing *lead*); (iv) stained floor areas in chemical or other industrial facilities (potentially containing toxic *pesticides, cleaning fluids, solvents, or other harmful chemicals*).

WARNING Preparation equipment is used to remove surface material from a variety of surfaces. The surface preparation process often generates large amounts of dust and other small particles, which are released into the air. WHEN A SURFACE CONTAINS HAZARDOUS MATERIALS, EXPOSURE TO THE DUST GENERATED BY THE PREPARATION EQUIPMENT MAY POSE A HEALTH RISK. INSPECT ALL SURFACES FOR POSSIBLE CONTAMINATES PRIOR TO USING PREPARATION EQUIPMENT AND CONSULT HAZARDOUS MATERIAL EXPERTS AND GOVERNMENT AUTHORITIES BEFORE OPERATING PREPARATION EQUIPMENT ON SURFACES SUSPECTED OF CONTAINING HAZARDOUS MATERIALS.

WARNING BW MANUFACTURING, INC. IN NO WAY REPRESENTS THAT ITS PREPARATION EQUIPMENT IS SUITABLE OR APPROVED FOR REMOVING HAZARDOUS MATERIALS FROM CONTAMINATED SURFACES. DO NOT ATTEMPT TO USE ANY PREPARATION EQUIPMENT MANUFACTURED BY BW MANUFACTURING, INC. ON ANY CONTAMINATED SURFACE. It is the responsibility of the preparation equipment operator and/or the contractor using the preparation equipment to inspect the proposed worksite for contaminants and obtain approval from contamination experts and/or government authorities before using BW Manufacturing, Inc. preparation equipment. It is also the responsibility of any contractor using preparation equipment to inform its employees or subcontractors of all potential health risks associated with operating preparation equipment and to ensure its employees or subcontractors are protected from exposure to harmful materials.

DIAMOND PRODUCTS LIMITED IS NOT RESPONSIBLE FOR ANY INJURY, ILLNESS, DEATH, OR PROPERTY DAMAGE THAT MAY RESULT FROM IMPROPER USE OF ITS PREPARATION EQUIPMENT OR OTHER PRODUCTS

DIAMIOND PRODUCTS

NEW FILTER APPLICATIONS

New filters will flow noticeable dust for the first 10 to 15 minutes of use or until the liter is adequately coated with material. The filters cleans to 99.950 efficiency at 2 microns and therefore the filter will allow a minimal amount of dust through the filter on every pulsation cycle even alter filter is fully loaded.

Further tests have shown that humidity and concrete dampness will affect the efficiency of the pulsation system to clean the filter.



2505797

HEPA

99.995% Efficiency@ .03 Microns



CV1900AV GAS VAC

Operating & Maintenance Instructions

Starting Instructions For Models Equipped With A Gas Engine

Begin by turning the gas valve to the OPEN position (1), then place the power switch in the ON position (2), adjusting the choke (3), place throttle in wide open position (4), and pull the starting handle (5). As motor begins to run you will need to adjust the choke (3) until the engine runs smoothly.

To turn off engine, start by placing the power switch (2) in the OFF position, and return the gas valve (1) to the CLOSE position.




Gas Engine Maintenance Instructions

Clean engine air filter every day
Change engine oil after first 20 hours of operation and every 100 afterward.

Starting Instructions For Models Equipped With An Electric Engine 220V Single Phase

Plug unit into a 220 volt, 30 amp service and turn on machine using ON/OFF Switch (6).



CV1900AV Operating & Maintenance Instructions

Attention:

Lift mount (A) MUST be installed before operating machine.



Torque bolts to 40 FT. LBS. (B)




CV1900AV

Operating & Maintenance Instructions

Greasing The Blower Bearing Housing

Grease every 8 hours (A)
With high temp silicone
grease




Filter Inspection & Maintenance

Routine inspection of filters (B)

To Clean Filter Manually:

Allow machine to run and pulsate, unattached to any equipment for approx. 10 – 15 min. This will allow the filter to clean its self of built up material. We suggest that you do NOT remove the filter until it need to be replaced.



*(Using filters that are **not designed** for collector systems will cause a decrease in vacuum).*



Gas Engine & Air Compressor Maintenance

Change oil every 100 hours of operation. Manufac-turer recommends 30 Weight Non-Detergent Oil in air compressor (G) and 10W-30 Oil in Honda En-gine (H).

Check air compressor air filter (I) and engine air filter (J) every 8 hours of operation.




CV1900AV Parts Air Group

To Set Pulsation Board

When power is **ON** the **"OFF"** will be displayed on the digital display.

To program:

1. Press **"SET"** and F02 will show on display. (A)
2. Press **"OK"** to show Solenoid Valve Activation Time. (D)
3. Press **"+"** or **"-"** to adjust to 0.05 (B or C)
4. Press **"OK"** to show solenoid pulse time (D)
5. Press **"+"** or **"-"** to adjust to 003 (B or C)
6. Press **"OK"** to show Number of Valves (D)
7. Press **"+"** or **"-"** to adjust to 02 (B or C)
8. Press **"OK"** (D)
9. Press **"SET"** and **OFF** will show on the display. (A)





CV1900AV

Operating & Maintenance

Instructions

Dust Drum Removal and Installation

To remove drum for emptying, start by turning the winch handle counter clockwise (1) to lower the drum. Once there is slack in the cable, unhook the pulley (2) from either side of the drum and push chassis of vacuum back. Once drum is clear of the chassis it is ready to be emptied of debris and dust.



(Shown with optional drum liner)

CV1900AV

Operating & Maintenance Instructions

Dust Filter Cleaning & Replacement.

Allow machine to run and pulsate, unattached to any equipment for approx. 10 – 15 min. This will allow the filter to clean its self of built up material. We suggest that you do NOT remove the filter until it needs to be replaced.


To determine if you have a bad dust filter.

Watch blower exhaust while the machine is in operation to determine if the filter needs to be replaced. When inspecting filters, if you find a layer of dust on the top of the filter inside the rubber seal ring, this is an indication that the filter is bad and needs to be replaced.



*(Using filters that are **not designed** for collector systems will cause a decrease in vacuum and will reduce paddle and liner life).*

Good Filter



Bad Filter




CV1900AV Parts

Body Group

- 1. 2506774 Belt Guard
- 2. 2505833 Wire Rope Clip
- 3. 2506767 Collector Lid
- 4. 2506771 Intake Assembly
- 5. 2505860 Caster (Stationary)
- 6. 2505862 Caster (Swivel) Timer
- 7. 2508910 Board Assembly




- 1. 2505838 Winch
- 2. 2506765 Collector Body
- 3. 2506157 Drum Assembly w/ Casters
- 4. 2505839 Pulley W/Hook
- 5. 2509773 Handle
- 6. 2506130 Fork Guard




CV1900AV Parts Body Group

- 1. 2506781 Lift Bracket
- 2. 2506777 Lid seal (*not shown*)
- 3. 2506757 Cap 5"
- 4. 2506771 Intake Pipe
- 5. 2505846 Lanyard
- 6. 2505859 Cap 2" x 2"
- 7. 2506778 Drum seal (*not shown*)
- 8. 2506770 Pulley
- 9. 2506769 Drum Strap




- 1. 2506772 Dust Deflector
- 2. 2505797 Filter (spun bond w/ PTFE coating) (*standard*)
- 3. 2505796 Filter (blend) (*optional*)
- 4. 2506764 Filter Nut




CV1900AV Parts Body Group

- 1. 2505868 Clutch (Gas)
- 2. 2505836 Idler Pulley
- 3. 2505832 Belt Tensioner
- 4. 2505864 Belt
- 5. 2505837 Blower Sheave
- 6. 2506775 Blower Mount




- 1. 2508911 Motor Sheave (220V)
- 2. 2505836 Idler Pulley
- 3. 2505832 Belt Tensioner
- 4. 2508912 Belt
- 5. 2505837 Blower Sheave Blower
- 6. 2506775 Mount




CV1900AV Parts Body Group


- 1. 2506756 Blower Fan (key #6010170)
- 2. 2508802 Blower Fan Bolt
- 3. 2506761 Blower Hub
- 4. 2505829 Blower Fan Bearing
- 5. 2505831 Blower Fan Main Shaft Snap Ring
- 6. 2506760 Blower Fan Main Shaft



CV1900AV Parts Air Group




- 1. 2506763 Air compressor filter
- 2. 2505840 Air Compressor
- 3. 2506768 Air Compressor Sheave
- 4. 2508913 Heat Deflector
- 5. 2508914 90 degree Adaptor
- 6. 2508915 Adaptor




5 Aerial view of heat deflector and filter

- 1. 2508916 Adapter
- 2. 2505825 Compressor Fitting
- 3. 2505873 Air Compressor Air
- 4. 2505822 Line Adapter
- 5. 2505852 Pipe Nipple (*not shown*)
- 7. 2505821 Breather




CV1900AV Parts Air Group

- 1. 2508917 Air Tank
- 2. 2508918 Poppet Valve
- 3. 2505851 Air Fitting (90 deg.)
- 4. 2505819 Pressure Relief Valve



- 1. 2505848 Orifice Bushing Poppet
- 2. 2508918 Valve
- 3. 2508805 Poppet Valve Repair Kit




CV1900AV Parts Electric Group

1

GAS MODEL ONLY

1. 2508920 Timer Board & Enclosure Timer
2. 2508919 Board Fuse
3. 2508921 Voltage Regulator
4. 2508922 Cushion Strap
5. 2508923 Battery
6. 2509103 Switch
7. 2508910 Timer Board Complete Assembly




1. 2508924 Solenoid Valve (not shown)
2. 2508925 Coil



CV1900AV

Additional Spare Parts



2505835
5" x 15' Vac Hose
(Standard)



2506155
2" x 15' Vac
Hose



2505797 (Standard)
Spun Bond Poly w/ PTFE
Coating 99.995% Efficiency
@ .03 Microns

2505796 (Optional)
Filter (Blend) (Standard)
99.7% Efficiency @ .05
Microns



2506156
30 Gallon Drum Liner
(4 mil)