



Customer: Hall County Government
Fleet Maintenance Dept.
1670 Barber Road
Gainesville, GA 30507

Contact: Michael Johnson
Phone: (770) 718-2349
Mobile: (770) 654-1430
Email: mdjohnson@hallcounty.org

Body Type: H7024TT-1-84

Chassis: 2022 Ford F550 Crew Cab 4x4

Quote Number: 9070

Quote Date: 07/26/2023

Salesperson: Ken Corder

Description

Cost Variance Modifier (CVM), meaning that if inflation continues to accelerate, we will have no choice but to requote prior to line drawing approval and release for production. In the alternative, you may cancel orders (with applicable fees) any time prior to manufacture. Dealers, be sure to include this and notify your customers of the CVM possibility.

Config # C21618

Chassis: Ford F550 4x4, Torq Shift 10 Speed Automatic, 84" CA, Diesel, Crew Cab

Factory Options Selected: Diesel Motor, Factory Backup Camera, Rear Spring Suspension, Exhaust, Single Fuel Tank

--- Maintainer Body ---

- Base price of Service body - 1-ton, 52" tall compartments, 44" x 21" wheel well opening with skirting (includes fuel fill pockets for chassis with mid-frame tanks as needed), front body bulkhead, body access grab handles, painted safety yellow (locations and number to vary with design)
- (11.083) Feet of Service Body - 1-ton, 52" tall Galvannealed compartments with reinforced floors, clean out drains, and 14 Gauge Deck Plate
- Factory Installation of body on a chassis. Note: On 2-ton chassis, we will no longer be modifying the dash for lights or switches. Will use OEM switches where applicable, any additional Maintainer switches will be on a bracket / panel mounted in separate location
- Tall Tower Crane reinforcement for MTS 1- or 2-ton service body (up to 75,000 ft*Lbs.) • Crane Location: Curb Side

--- Chassis Equipment & Accessories ---

- Spring or spacer leveling package added to one side of chassis suspension (1-Ton)
- Electronic engine speed control - computer set - electronic engine
- 2.5 lb. ABC fire extinguisher, and hazard reflectors
- Back up alarm - 97 dB at 1 meter
- Camera, relocate existing chassis camera to rear of body Note: Requires factory installed monitor

--- Hydraulic Power Package ---

- Open center hydraulic power package NOTE: The Open-Center hydraulic system allows operation of only a single hydraulic component at a time. Multi-component operation requires a Closed-Center system and is not available on some chassis configurations. Contact the factory for details. Contains HP Filter
- Open center hydraulic system pump (Chelsea) includes pressure reducer
- Oil reservoir - complete #022265, composite 28 gallons; Tank only, excluding oil
- (28) Hydraulic Oil (Standard oil, per gallon) Oil good for -25° F startup and 9° F to 187° F operating temperature
- No Reservoir Heater was selected.
- PTO for electric-over-hydraulic required on chassis with automatic transmission. (Ford F450-F550-F600, F650-F750 & Ram4500-5500)

--- Welder / Generator / Inverter / Power Equipment ---

- Mounting angles, 45" long Includes mounting holes for common welder types (contact factory for compatible welders)

--- Air Compressor Equipment & Accessories ---

- VMAC Predatair 40 CFM rotary screw hydraulic driven air compressor w/ white cover (Open-Center) 40 CFM @ 150 psi with integral hydraulic oil cooler. Includes control panel, mounted near body's switch panel & Hydraulic Soft Start Note: Hydraulic requirement = 14 GPM (May require large pump kit, not included), Cold weather package included (cooler bypass), additional oil warming valve available 24"L x 16.5"W x 18"H, 162 Lbs.
- Mounting angles for Air Compressor
- Air tank - 17 gallon - (Pressure rating of 200 psi) / 16" diameter (000012) Includes moisture drain, Painted Black
- Air accessory package - 1/2" X 50', spring rewind reel, hose & ball stop
- 1/2" Filter, Regulator, and Lubricator (FRL)
- Fiber box; Hose reel access, Limit 1 Reel Per Fiber box

--- Outriggers & Accessories ---

- Outriggers for cranes up to 45,100 ft*Lbs., hydraulic up/down rear outriggers (2) with manual extend in/out on crane side (30" extend)
- Outrigger pads, permanent (welded-on)

--- Compartment Equipment & Accessories ---

- Pressurized Storage System (PSS), 2-blowers with filters
- CS2 Mount Oxy bottles on left side of compartment

--- Street Side Vertical Compartment #1 ---

- Dimensions:52" Tall X35" Wide X23" Deep
- 12-Volt LED strip light
- Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- (2) Door Gas spring 65# (003184)
- DualLock or Bolt Bin - See configuration details below (page 5 of 6)

--- Street Side Vertical Compartment #2 ---

- Dimensions:52" Tall X24" Wide X23" Deep
- 12-Volt LED strip light
- Reverse Hinged 3/16" Aluminum, Single Door, Included Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- Door Gas spring 65# (003184)
- (2) Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed

--- Street Side Overwheel Compartment ---

- Dimensions:31" Tall X44" Wide X23" Deep
- 12-Volt LED strip light
- Single 3/16" Aluminum "hinge-up" Door, Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- (2) Door Gas spring 60#
- Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed

--- Street Side Rear Vertical Compartment ---

- Dimensions:52" Tall X30" Wide X23" Deep
- 12-Volt LED strip light
- Single 3/16" Aluminum Vertical hinge door, Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- Door Gas spring 65# (003184)
- (2) Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed

--- Curb Side Vertical Compartment #1 ---

- Dimensions:59" Tall X35" Wide X23" Deep
- Above standard compartment height cost
- 12-Volt LED strip light
- Vertical Double 3/16" Aluminum Doors (French Style), Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- (2) Door Gas spring 65# (003184)
- (2) Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed

--- Curb Side Vertical Compartment #2 ---

- Dimensions:59" Tall X24" Wide X23" Deep
- Above standard compartment height cost
- Reverse Hinged 3/16" Aluminum, Single Door, Included Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- Door Gas spring 65# (003184)
- 12-Volt LED strip light
- 2 Oxy/Act Bottle Storage Kit, contains Ratchet Strap, Vents in door, (2) "J" Hooks, reinforced floor (Protective spray coated) and mounting side brackets

--- Curb Side Overwheel Compartment ---

- Dimensions:31" Tall X44" Wide X23" Deep
- 12-Volt LED strip light
- Single 3/16" Aluminum "hinge-up" Door, Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch
- (2) Door Gas spring 60#
- Shelf, aluminum adjustable compartment shelf (250 Lbs. capacity) - Installed

--- Curb Side Under Crane Compartment ---

- Dimensions:15" Tall X30" Wide X12" Deep
- Single 3/16" Aluminum "hinge-down" Door, Includes Rubber Seal
- Standard Compartment 3-Point "D Ring" Door Latch

--- Lighting / Electrical Equipment & Accessories ---

- Base electrical components - Can System Includes Wiring Harnesses, Power Distribution Module, & Main Body Controller• 4.3" display CAN switch panel
- ~Grote FMVSS 108 LED lighting / reflector Kit: (2) Oval S/T/T/R, (2) Oval S/T/T, (5) Red 3/4" Marker lights, (2) Amber 3/4" Marker lights
- (5) Exterior 12-Volt LED flood light 022232 (2,100 Lumens)
- ~Strobe Lighthoods, L.E.D, oval, amber, recessed, 6.5" x 2.25" (pair)

--- Paint, Undercoating, & Protective Spray Coating (PSC) ---

- (11.083) Feet of Unit Painted Urethane "White" color. Not a base coat/clear coat or Metallic• (11.083) Feet of Primer
- (11.083) Feet of Splatter Coating on interior of compartments
- (11.083) Feet of Undercoat
- PSC- Level 30• Compartment Fronts • Bottoms of door frames • Outside wheel wells • Bumper sides, step Face & Top • Outer outrigger tubes • Center deck floor – includes Welder Deck, and bumper vertical surfaces • Cargo side walls includes Bulkhead • Compartment Tops – includes any brackets or guards welded to the top •Bumper top surface
- Install and stamp customer supplied metal name plate with WO# and Model#

--- Center Deck Equipment & Accessories ---

- Center Deck Dimensions:133" Long X49" Wide X1/8" Thickness
- (11.083) ~1/8" Cargo floor (deck plate)
- 10" Tall hinge-down "Slam Latch" Aluminum tailgate (12" total Height, 10" tall above deck) (protective spray front, black paint on rear)
- 10" Tall tailgate extension panel (Paint/PSC Follows Cargo Sidewall)
- (6) Flush mount "D" ring tie-downs in bed floor #003217

--- Rear Bumper & Accessories ---

- 26" steel workbench bumper with recessed step on curb side, 1 storage compartment. Includes: Bolt on Yellow grab handles and strip light for recessed step safety
- ~Bumper surface 3/16" smooth
- ~Transverse bar storage compartment in workbench bumper flush to the floor
- Vise / grinder removable mounting plate HD, includes drain slots in plate
- Class IV hitch receiver - 2" receiver - rated at 1,500 Lbs. vert. 10,000 Lbs. Includes Safety Chain loops MGTW Note: customer is responsible to verify tow ratings of chassis and available GVWR/GCWR remaining after loading of body and all other items.
- Trailer plug-in 7-prong flat blade #007486 (RV style)
- Step, Bolt-on, flexible sides with stainless steel step, Painted Safety Yellow #026127 (standard step)

--- Miscellaneous Equipment & Accessories ---

- Install customer supplied mudflaps
- Mud flap bracket for a 24" mudflap
- Parts and service manual

---Additional Equipment Installed ---

- TTC-M3PWG Lube Skid
- Miller Bobcat 260 Gas
- 50' Leads & Clamps
- Remote Start / Stop
- Body Level

---Maintainer Crane---

Config # C21619

- H7024TT Crane 7,000 Lbs. max capacity (45,100 ft*Lbs.) with hydraulic extend hex-boom 11'-24' Note: Max capacity listed above is for 2-part line, for single-part line max capacity is 4,300 Lbs. Crane includes A2B, overload system, holding valves ACC 2.1 (crane lifting weight display, capacity & speed limiting, stability monitoring, warn / stop feature) Paint note: Ship-out crane-only: Requires additional paint charge Crane installed on body: No additional paint charge unless different color than body MIN GVW REQUIRED : 19,500
- Install hydraulic crane on body - includes boom saddle, and valve well with HD reinforced cover
- ~Load Block (No live swivel) H6-H10
- Planetary winch (H6-H7) T11
- Crane remote, wireless, push button (H6-H14), with true independent proportional control, includes holder, external antenna, hour meter, engine start/stop
- Backup cable for wireless crane remote, 35ft (#022585)
- Annual crane inspection (initial inspection) • Paint Crane to match Service Body

---Street Side Vertical #1 Dualock---

Config # C21620 Design Style: (7) drawer set #020017 (29" wide)

Housing Dimensions:41.5" Tall, 29" Wide, 18" Deep

Top Shelf is Standard, Drawers Listed from Top to Bottom

Drawer #	Height	Dividers
Drawer 1	3"	Side to Side
Drawer 2	3"	Side to Side
Drawer 3	3"	Side to Side
Drawer 4	5"	Side to Side
Drawer 5	5"	Side to Side
Drawer 6	5"	Side to Side
Drawer 7	7"	Side to Side

BOTTOM SPACE: 7.0 Inches Tall

---Notes---

Bolt on step to ship loose with unit

Houston Automotive Group Terms and Conditions

- All prices are F.O.B. Houston, TX & in USD; delivery charges to be determined. This quote does not include any applicable local, state or (F.E.T) federal taxes. Payment is required on or before delivery unless other terms are agreed upon before sale.
- Ex-factory delivery is 14-21 days after receipt of order with full order information subject to prior sales and chassis availability.
- Houston Automotive Group reserves the right to make changes and/or substitute components and product is subject to change without notice; Houston Automotive Group is not responsible for any Local, State, Federal or other regulations that maybe pertinent to quote/order.
- The information contained in this quote, and all supporting documentation is confidential and may only be used by Houston Automotive Group, our manufacturer and/or the customer listed on this quote.
- We assume no liability for damage due to theft, vandalism, fire, weather, disaster, or damage due to gradual deterioration or inherent defect in such property.
- We assume no liability for damage of any kind during the storage of your chassis or parts on our premises while awaiting modification or installation. The storage location of the property shall be determined by Houston Automotive Group in its discretion.
- Exception to above is when directly attributable to our own gross negligence in moving or modifying chassis or parts, and in that event only to the extent of the wholesale used value of the chassis or parts as of the date of storage.

Please contact me with any questions or concerns at (281) 807-6500.

We appreciated the opportunity to quote you. Please show acceptance by signing below and faxing back to me at (281) 807-5322.

Sincerely,
Ken Corder
Truck & Equipment Sales
Houston Automotive Group, Inc.
(281) 807-6500

Quote#: 9070
Order Acknowledgement / Authorization:
Hall County Government

x _____
Michael Johnson