

Quote Provided By
 JAMES SHORT TRACTOR &
 EQUIPMENT OF
 Neil King
 1325 STATE HIGHWAY 365
 ALTO, GA 30510
 email: neilking1@live.com
 phone: 7067789000

-- Standard Features --

-- Custom Options --



K Series KX057-5R3AP

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

7" LCD Color Display
 Auto Idler
 Rubber Track Models
 A/C ROPS/OPG Cab
 Kubota 3 Hydraulic Pump Load Sensing System
 1 Gear, 2 Variable Displacement Pumps
 All Controls Hydraulic Pilot Controls
 Two Operating Pattern Selection System
 Accumulator
 Digital Control Panel
 Attachment Flow Presets, Service Alerts
 Standard Front Dozer Blade w/ Float
 360 Degree Full Rotation
 70 Degree Left, 55 Degree Right Boom Swing
 19.8 gpm Adjustable Auxiliary Hydraulics Port 1
 Auxiliary Hydraulics Diverter Valve
 Thumb Bracket and Relief Valves
 Five Second Quick Preheat System
 Key Switch Stop System
 Half Pitch Rubber Tracks
 Self Bleed Fuel System
 Auto-Downshift Two Speed Travel System
 Swivel Negative Brake
 Travel Negative Brake
 Third Line

ENGINE

V2607 Kubota CR E5 Tier 4 Diesel Engine
 4 Cylinder, 4 Cycle
 46.4 Net HP @ 2200 rpm (SAE J1349)

OPERATIONAL

DIMENSIONS
 Max Digging Depth 12' 9"
 Max Digging Radius @ Ground Level 20' 1"
 Max Vertical Digging Depth 5' 4"
 Max Dumping Height 13' 8.6"

DOZER BLADE

DIMENSIONS
 Width 77.2"
 Height 16.1"
 Lift Above Ground 17.3"
 Drop Below Ground 15.9"

PERFORMANCE

Digging Force @
 Bucket 10,172 lbs.
 Digging Force @ Dipper Arm 5,463 lbs.
 Travel Speed (Low) 1.7 mph
 Travel Speed (High) 3.0 mph
 Climbing Ability 36% / 20°
 Lift Capacity 3,410 lbs.
 Over Front
 Blade Grounded
 4.0 Ft. Load Point Height
 12.0 Ft. Load Radius

STANDARD WARRANTY

Basic Warranty - 24 Months / 2000 Hours
 Rubber Track Warranty - 12 Months / 1000 Hours

DIMENSIONS AND OPERATING WEIGHT

KX057-5R3AP, Rubber Tracks, ROPS/OPG (Top Guard, Level I) Cab,
 Angle Dozer Blade, Dipper Arm, Counterweight, SP2
 Overall Length 18' 1.3"
 Overall Width 6' 5.2"
 Overall Height 8' 4.4"
 Operating Weight 13,051 lbs.*
 Ground Clearance 12' 0.2"

*Includes operator's weight, 165 lbs.

KX057-5R3AP Base Price: \$92,971.00

(1) 12" QA TRENCHING BUCKET/U55/KX057-4 K7917-12" QA TRENCHING BUCKET/U55/KX057-4	\$1,514.00
(1) MIRROR KIT/CAB/KC040/U35/U55/KX057 K7479-MIRROR KIT/CAB/KC040/U35/U55/KX057	\$264.00
(1) HYDRUALIC THUMB K7937B-HYDRUALIC THUMB	\$3,294.00
(1) BKT Q.A. COUPLER FOR U55/KX057-4 K7915-BKT Q.A. COUPLER FOR U55/KX057-4	\$1,335.00
(1) 36"Q.A. TRENCHING BCKT/U55/KX057-4 K7921-36"Q.A. TRENCHING BCKT/U55/KX057-4	\$2,839.00

Configured Price:	\$102,217.00
Sourcewell Discount:	(\$24,532.08)
SUBTOTAL:	\$77,684.92
Dealer Assembly:	\$165.00
Freight Cost:	\$850.00
PDI:	\$400.00

Total Unit Price:	\$79,099.92
Quantity Ordered:	1
Final Sales Price:	\$79,099.92

Final pricing will be based upon pricing at the time of final delivery to Sourcwell members. Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting dealer

**Some series of products are sold out for 2022. All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.*