



Utility Tractors & Mowers - 031121
CE and AG - 040319
Utility Vehicles 122220
Arkansas 4500041718
Delaware 055-21673
Mississippi (CE Only) 8200056371
Mississippi 8200055841

SVL97-2HFC WEB QUOTE #2681419

Date: 6/14/2023 9:32:11 AM

— Customer Information —

Hall County Road Maintenance, Hall County Road

Maintenance

Hall County Road Maintenance

jhightower@hallcounty.org

770-531-6824

Quote Provided By
MASON TRACTOR & EQUIPMENT CO.,
INC.
Randy Thompson

— Standard Features —



S Series SVL97-2HFC
*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Final Tier 4 Certified Kubota
Diesel Engine
Electronic Travel Torque
Management System
Vertical Lift Path Loader Frame
Standard Front Quick Coupler,
Float Standard
Hydraulic Quick Coupler Option
Loader Arm Self-Leveling
Loader Boom Lock
Open ROPS/FOPS
Optional enclosed and
pressurized cab with A/C
High Back, Adjustable, Vinyl,
Suspension Seat
2" Retractable Seat Belt And 2-
Piece Seat Bar
23.1 gpm Auxiliary Hydraulics
Standard, 40.0 gpm Option
Case Drain Line
Rigid Mounted Undercarriage, 5
Lower Track Rollers
High Grip Rubber Tracks, 17.7"
Standard
Two Speed Travel System
Automatic Wet Disk Parking
Brake
Kubota 4 Hydraulic Pump Load
Sensing System
2 Variable Displacement
Pumps
Rearview Camera
KubotaNOW Telematics
Lockable DEF Cap Guard
Hydraulic Joystick Controls
ISO Operating Pattern
Dial Knob and Foot Throttle
Controls
Stall Guard Engine Controls
Automatic Glow Plugs
Key Switch Stop System
Self Bleed Fuel System
2 Front and 2 Rear Working
Lights
Hour Meter, Engine Temperatur,
DEF, and Fuel Gauges and
Warning Lights
Lockable DEF Tank Cap
Lockable Fuel Cap
Radio Ready on Enclosed
Cabs

BASIC UNITS

SVL97-2S, 17.7" Rubber Tracks,
Open ROPS/FOPS Cab
Quick Coupler
OPERATIONAL
DIMENSIONS
Operating Weight*, SVL97-2s,
17.7" Rubber Tracks, Open
ROPS/FOPS Cab,
Mechanical Quick Coupler 11,299
lbs.
Rated Operating Capacity (ROC)
@ 35%
of Tipping Load complies with ISO
14397-1
and SAE J 818) 3,200 lbs.
Rated Operating Capacity (ROC)
@ 50%
of Tipping Load 4,572 lbs.
Tipping Load 9,143 lbs.
Auxiliary Hydraulics Flow 24 / 40.0
gpm
Travel Speed (Low / High) 5.0 / 7.3
mph
Reach @ Maximum Height 40.7'
Height to Hinge Pin 128.6"
Ground Pressure 4.5 psi.
Traction Force 12,178 lbf.

* Includes operator's weight, 175
lbs.
ENGINE
V3800-Tier 4 Kubota Final Tier 4
Diesel Engine
4 Cylinder, 4 Cycle, Turbo Charged
96.0 Gross HP @ 2400 rpm

DIMENSIONS
Cab Height 83.4"
Width (without attachment) 77.2"
Length (without attachment) 123.5"
Length of Track on Ground 65.6"

— Custom Options —

SVL97-2HFC Base Price: \$91,154.00

(1) SVL REAR VIEW CAMERA KIT inc.
S6780-SVL REAR VIEW CAMERA KIT

(1) SVL TELEMATICS HARNESS inc.
S6702-SVL TELEMATICS HARNESS

(1) AT&T TELEMATICS MODEM inc.
DCU6700-AT&T TELEMATICS MODEM

(1) 80" HVY DUTY /LW PRF/LONG FLR/TEETH \$2,556.00
PNF
AP-HD80LLT-80" HVY DUTY /LW PRF/LONG FLR/TEETH PNF

Configured Price: \$93,710.00

Sourcewell Discount: (\$22,490.40)

SUBTOTAL: \$71,219.60

Dealer Assembly: \$0.00

Freight Cost: \$831.25

PDI: \$400.00

Total Unit Price: \$72,450.85

Quantity Ordered: 1

Final Sales Price: \$72,450.85

Final pricing will be based upon pricing at the time of
final delivery to Sourcewell members.
Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting
dealer

*Some series of products are sold out for 2022. All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.