

SVL97-2HFC WEB QUOTE #2804447 Date: 8/16/2024 7:04:55 AM -- Customer Information --**BOLLINGER, TIM** 10621 HALL COUNTY BOC tbollinger@hallcounty.org 470-691-4140

Quote Provided By JAMES SHORT TRACTOR & **EQUIPMENT OF** Neil King 1325 STATE HIGHWAY 365 ALTO, GA 30510 email: neilking1@live.com phone: 7067789000

-- Standard Features --



S Series

* * * EQUIPMENT IN STANDARD MACHINE * * *

FEATURES

Final Tier 4 Certified Kubota

Diesel Engine Electronic Travel Torque

Management System Vertical Lift Path Loader Frame OPERATIONAL

Standard Front Quick Coupler, Float Standard

Hydraulic Quick Coupler Option Loader Arm Self-Leveling

Loader Boom Lock

Open ROPS/FOPS Optional enclosed and pressurized cab with A/C High Back, Adjustable, Vinyl,

Suspension Seat 2" Retractable Seat Belt And 2-Piece Seat Bar

23.1 gpm Auxiliary Hydraulics Standard, 40.0 gpm Option

Case Drain Line Rigid Mounted Undercarriage, 5 Auxiliary Hydraulics Flow 24 / 40.0 Lower Track Rollers

High Grip Rubber Tracks, 17.7" Standard

Two Speed Travel System Automatic Wet Disk Parking

Brake Kubota 4 Hydraulic Pump Load

Sensing System 2 Variable Displacement **Pumps**

Rearview Camera KubotaNOW Telematics Lockable DEF Cap Guard

Hydraulic Joystick Controls ISO Operating Pattern Dial Knob and Foot Throttle Controls

Stall Guard Engine Controls Automatic Glow Plugs Key Switch Stop System Self Bleed Fuel System 2 Front and 2 Rear Working Liahts

Hour Meter, Engine Temperatur, DEF, and Fuel Gauges and

Warning Lights Lockable DEF Tank Cap Lockable Fuel Cap Radio Ready on Enclosed Cabs

BASIC UNITS

SVL97-2S, 17.7" Rubber Tracks, Open ROPS/FOPS Cab Quick Coupler

DIMENSIONS

Operating Weight*, SVL97-2s, 17.7" Rubber Tracks, Open ROPS/FOPS Cab, Mechanical Quick Coupler 11,299 lbs. Rated Operating Capacity (ROC) @ 35%

of Tipping Load complies with ISO

14397-1 and SAE J 818) 3,200 lbs.

Rated Operating Capacity (ROC) @ 50%

of Tipping Load 4,572 lbs. Tipping Load 9,143 lbs.

apm

Travel Speed (Low / High) 5.0 / 7.3 mph

Reach @ Maximum Height 40.7" Height to Hinge Pin 128.6" Ground Pressure 4.5 psi.

Traction Force 12,178 lbf.

* Includes operator's weight, 175

ENGINE

V3800-Tier 4 Kubota Final Tier 4 Diesel Engine 4 Cylinder, 4 Cycle, Turbo Charged 96.0 Gross HP @ 2400 rpm

DIMENSIONS

Cab Height 83.4"

Width (without attachment) 77.2" Length (without attachment) 123.5" Length of Track on Ground 65.6"

SVL97-2HFC Base Price: \$92,961.00

(1) SVL TELEMATICS HARNESS inc. S6702-SVL TELEMATICS HARNESS (1) SVL REAR VIEW CAMERA KIT inc. S6780-SVL REAR VIEW CAMERA KIT

-- Custom Options --

(1) 80" Heavy Duty, Low Profile, Long Floor, Side \$2,702.00 Cutter and Bolt-on Cutting Edge, 21.3 cu-ft heaped capacity

S6606-80" Heavy Duty, Low Profile, Long Floor, Side Cutter and Bolt-on Cutting Edge, 21.3 cu-ft heaped capacity

(1) 14 PIN TO 14 PIN ADAPTER \$606.00 S6650-14 PIN TO 14 PIN ADAPTER

(1) HOSE STAY FOR SSV/SVL MODELS \$108.00 S6763-HOSE STAY FOR SSV/SVL MODELS (1) SVL LED LIGHT KIT \$392.00

S6764-SVL LED LIGHT KIT (1) AT&T TELEMATICS MODEM \$449.00

DCU6700-AT&T TELEMATICS MODEM

(1) AIR RIDE SEAT SUSPENSION KIT \$690.00 S6679-AIR RIDE SEAT SUSPENSION KIT

Configured Price: \$97,908.00 Sourcewell Discount: (\$23,497.92)

SUBTOTAL: \$74,410.08

Dealer Assembly: \$568.33 Freight Cost: \$887.50

PDI: \$400.00

> Total Unit Price: \$76,265.91 Quantity Ordered:

Final Sales Price: \$76,265.91

Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting dealer