



VIP Series™ Pneumatic Test Plugs

Reliable and field tested technology for DWV pressure testing.

Test-Tite® has introduced a new addition to our DWV test plugs family with the innovative single-size pneumatic plug design. The latest VIP Series™ test plugs are available in four different nominal sizes; 1-1/2", 2", 3" and 4" with 1 ft. chain. The 3- and 4-inch plugs are also available with a 6 ft. chain. This groundbreaking process utilizes our proprietary production method, ensuring an elevated level of product precision and performance.

The manufacturing process involves cutting-edge presses equipped with digital controllers, facilitating precise vulcanization of the natural rubber body. This advanced technique contributes to the overall quality of the product. At Test-Tite, we remain committed to offering a comprehensive range of test plugs. Our offerings include long, large, and multi-size plugs, along with pumps and extension hoses to cater to diverse testing needs.



PRODUCT	DESCRIPTION	MODEL	UNITS/CASE
Standard Packs			
83551	1-1/2" Pneu. Plug w/1 ft Chain	83551	6
83552	2" Pneu. Plug w/1 ft Chain	83552	6
83553	3" Pneu. Plug w/1 ft Chain	83553	6
83554	4" Pneu. Plug w/1 ft Chain	83554	6
83556	3" Pneu. Plug w/6 ft Chain	83556	6
83557	4" Pneu. Plug w/6 ft Chain	83557	6
Accessories			
83692	2-Ft. Extension Hose	83692	6
83693	3-Ft. Extension Hose	83693	6
83695	5-Ft. Extension Hose	83695	6
83700	Black Pump w/Gauge – High-Impact Plastic Body	83700	1
83710	Red Pump w/Gauge –Steel Body	83710	1

- ① High-performance Schrader valve compatible with traditional air pumps. Metal valve cap with intricate core removal feature is provided.
- ② Quality control testing on **every** test plug. Every plug is inflated for a duration of 30 minutes to test its integrity.
- ③ Highest quality tested natural rubber from a global raw material compounder with ISCC Plus certification.
- ④ The plug design has evenly spaced "sealing ribs" to enhance traction to the pipe wall. These sealing ribs prevent slippage of the test plug when pressure is applied.
- ⑤ Vulcanization In-Mold Process with state-of-the-art precision molding vulcanization presses and automated PLC programmable temperature and mold controls.

- ⑥ The VIP Series™ Pneumatic Test Plug features a long valve stem so the retaining band will not slip off the plug.
- ⑦ Ring tag handle is made of durable ABS plastic and will not rust like metal rings. In addition, it is sized to a diameter greater than the pipe so it cannot fall into the pipe. Finally, the handle features a "comfort grip" for easy removal of the test plug.
- ⑧ The galvanized steel sash chain is lightweight, rust resistant, and kink proof.

Leading industry 30-month warranty from time of manufacturer against manufacturer's defects.

Supporting accessories include extension hoses, inflation hoses, and gauges.

