

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### 1 Identification

#### 1.1 Product identifier

Trade name **WELD-ON 771 YELLOW**  
Product category/ies Low VOC Solvent Cement for ABS Plastic Pipe

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses adhesive  
ABS Solvent Cement

#### 1.3 Details of the supplier of the safety data sheet

Weld-On  
17109 S. Main  
Gardena CA 90248-3127  
United States

Telephone: 1-310-898-3300  
e-mail: EHSInfo@ipscorp.com  
Website: www.weldon.com

#### 1.4 Emergency telephone number

Emergency information service 24 Hours - CHEMTEL: (800) 255-3924; International (813) 248-0585

### 2 Hazard identification

#### 2.1 Classification of the substance or mixture

Classification acc. to GHS

Hazard class	Category
flammable liquid	2
serious eye damage/eye irritation	2
specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

#### 2.2 Label elements

Labeling

- Signal word danger

- Pictograms

GHS02, GHS07



## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### - Hazard statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### - Precautionary statements

P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to industrial combustion plant.

- Hazardous ingredients for labelling methyl ethyl ketone, acetone

### 2.3 Other hazards

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

## 3 Composition/ Information on ingredients

### 3.1 Substances

Not relevant (mixture)

### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
methyl ethyl ketone	CAS No 78-93-3	30 - < 60	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336
acetone	CAS No 67-64-1	10 - < 30	Flam. Liq. 2 / H225 Eye Irrit. 2 / H319 STOT SE 3 / H336

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

Name of substance	Identifier	Wt%	Classification acc. to GHS
styrene	CAS No 100-42-5	< 0.1	Flam. Liq. 3 / H226 Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Repr. 2 / H361d STOT SE 3 / H335 STOT RE 1 / H372 Asp. Tox. 1 / H304

### Remarks

For full text of abbreviations: see SECTION 16

## 4 First-aid measures

### 4.1 Description of first-aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

### 4.3 Indication of any immediate medical attention and special treatment needed

none

## 5 Fire-fighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

#### Unsuitable extinguishing media

Water jet

### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

Flash point 1.4 °F

### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

## 6 Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

## 7 Handling and storage

### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedings.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Managing of associated risks

##### - Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

##### - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

##### - Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

##### - Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## 8 Exposure controls/ Personal protection

### 8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
CA	styrene, monomer	100-42-5	OEL (BC)	20		40					"BC Regulation"
CA	styrene, monomer	100-42-5	OEL (ON)	35		100					Regulation 833
CA	styrene, monomer	100-42-5	OEL (ON-MoL)	35		100					MoL
CA	styrene, monomer	100-42-5	PEV/VEA		50	75					Regulation OHS
CA	Styrene, monomer (Phenylethylene; Vinyl benzene)	100-42-5	OEL (AB)	20	85	40	170				OHS Code
CA	cyclohexanone	108-94-1	OEL (AB)	20	80	50	200			H	OHS Code
CA	cyclohexanone	108-94-1	OEL (BC)	20		50				H	"BC Regulation"
CA	cyclohexanone	108-94-1	OEL (ON-MoL)	20		50				H	MoL

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
CA	cyclohexanone	108-94-1	PEV/VEA	25	100					H	Regulation OHS
CA	acetone	67-64-1	OEL (AB)	500	1,200	750	1,800				OHS Code
CA	acetone	67-64-1	OEL (BC)	250		500					"BC Regulation"
CA	acetone	67-64-1	OEL (ON-MoL)	250		500					MoL
CA	acetone	67-64-1	PEV/VEA	250		500					Regulation OHS
CA	2-butanone (methyl ethyl ketone)	78-93-3	OEL (AB)	200	590	300	885				OHS Code
CA	methyl ethyl ketone (MEK)	78-93-3	OEL (BC)	50		100					"BC Regulation"
CA	methyl ethyl ketone (MEK)	78-93-3	OEL (ON-MoL)	200		300					MoL
CA	methyl ethyl ketone (MEK)	78-93-3	PEV/VEA	50	150	100	300				Regulation OHS

#### Notation

Ceiling-C

H

STEL

TWA

ceiling value is a limit value above which exposure should not occur

absorbed through the skin

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

### Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
methyl ethyl ketone	78-93-3	DNEL	600 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
methyl ethyl ketone	78-93-3	DNEL	1,161 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	1,210 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
acetone	67-64-1	DNEL	2,420 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
acetone	67-64-1	DNEL	186 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
styrene	100-42-5	DNEL	85 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### Relevant DNELs of components

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
styrene	100-42-5	DNEL	289 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - systemic effects
styrene	100-42-5	DNEL	306 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
styrene	100-42-5	DNEL	406 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

### Relevant PNECs of components

Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
methyl ethyl ketone	78-93-3	PNEC	55.8 mg/l	aquatic organisms	freshwater	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	55.8 mg/l	aquatic organisms	marine water	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	709 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	284.7 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	284.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
methyl ethyl ketone	78-93-3	PNEC	22.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
acetone	67-64-1	PNEC	10.6 mg/l	aquatic organisms	freshwater	short-term (single instance)
acetone	67-64-1	PNEC	1.06 mg/l	aquatic organisms	marine water	short-term (single instance)
acetone	67-64-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
acetone	67-64-1	PNEC	30.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
acetone	67-64-1	PNEC	3.04 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
acetone	67-64-1	PNEC	29.5 mg/kg	terrestrial organisms	soil	short-term (single instance)
styrene	100-42-5	PNEC	0.028 mg/l	aquatic organisms	freshwater	short-term (single instance)
styrene	100-42-5	PNEC	0.014 mg/l	aquatic organisms	marine water	short-term (single instance)
styrene	100-42-5	PNEC	5 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
styrene	100-42-5	PNEC	0.614 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

Relevant PNECs of components						
Name of substance	CAS No	Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
styrene	100-42-5	PNEC	0.307 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
styrene	100-42-5	PNEC	0.2 mg/kg	terrestrial organisms	soil	short-term (single instance)

### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## 9 Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Color	yellow
Odor	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	56.05 °C
Flammability	flammable liquid in accordance with GHS criteria



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

Lower and upper explosion limit	not determined
Flash point	-17 °C
Auto-ignition temperature	465 °C (auto-ignition temperature (liquids and gases))
Decomposition temperature	not relevant
pH (value)	not determined
Solubility(ies)	not determined

### Partition coefficient

Partition coefficient n-octanol/water (log value)	this information is not available
---	-----------------------------------

Vapor pressure	240 hPa at 20 °C
----------------	------------------

### Density and/or relative density

Density	0.9 g/cm <sup>3</sup> at 73 °F
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

### Other safety parameters

Flash point	1.4 °F
-------------	--------

## 9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

### Other safety characteristics

- VOC content	When applied as directed, per SCAQMD Rule 1168, Test Method 316A, VOC content is: <= 325 g/L
Temperature class (USA, acc. to NEC 500)	T1 (maximum permissible surface temperature on the equipment: 450°C)

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### 10 Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### 11 Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to GHS

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if swallowed.

#### Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
styrene	100-42-5	inhalation: vapour	11 mg/l/4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

### Carcinogenicity

Shall not be classified as carcinogenic.

### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## 12 Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance at a concentration of  $\geq 0.1\%$ .

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of  $\geq 0.1\%$ .

### 12.7 Other adverse effects

Data are not available.

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### 13 Disposal considerations

#### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

### 14 Transport information

#### 14.1 UN number

UN RTDG	UN 1133
IMDG-Code	UN 1133
ICAO-TI	UN 1133

#### 14.2 UN proper shipping name

UN RTDG	ADHESIVES
IMDG-Code	ADHESIVES
ICAO-TI	Adhesives

#### 14.3 Transport hazard class(es)

UN RTDG	3
IMDG-Code	3
ICAO-TI	3

#### 14.4 Packing group

UN RTDG	II
IMDG-Code	II
ICAO-TI	II

#### 14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

#### 14.6 Special precautions for user

There is no additional information.

#### 14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### Information for each of the UN Model Regulations

#### Transport information - National regulations - Additional information (UN RTDG)

UN number	1133
Class	3
Packing group	II
Danger label(s)	3



Special provisions (SP)	- (UN RTDG)
Excepted quantities (EQ)	E2 (UN RTDG)
Limited quantities (LQ)	5 L (UN RTDG)

#### International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	- (not hazardous to the aquatic environment)
Danger label(s)	3



Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	B

#### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s)	3
-----------------	---



Special provisions (SP)	A3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

## 15 Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

#### National regulations (United States)

**Toxic Substance Control Act (TSCA)** all ingredients are listed as ACTIVE



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### Superfund Amendment and Reauthorization Act (SARA TITLE III )

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
styrene	100-42-5		1987-01-01

### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methyl ethyl ketone	78-93-3		4	5000 (2270)
acetone	67-64-1		4	5000 (2270)
styrene	100-42-5		1 3	1000 (454)

#### Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
methyl ethyl ketone	78-93-3		ATSDR Neurotoxicants CA TACs OEHHHA RELS
acetone	67-64-1		ATSDR Neurotoxicants
styrene	100-42-5		ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(d) IARC Carcinogens - 2A IRIS Neurotoxicants NTP 13th RoC - reasonable OEHHHA RELS Prop 65

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
methyl ethyl ketone	78-93-3				1.0 %
acetone	67-64-1				1.0 %
styrene	100-42-5				0.1 %

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### - Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
methyl ethyl ketone	78-93-3	A, N, O	
acetone	67-64-1	A, N, O	

#### Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
methyl ethyl ketone	78-93-3		F3
acetone	67-64-1		F3
styrene	100-42-5		CA F3 R2

#### Legend

- CA Carcinogenic
- F3 Flammable - Third Degree
- R2 Reactive - Second Degree

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
2-BUTANONE	78-93-3	E
2-PROPANONE	67-64-1	E

#### Legend

- E Environmental hazard

### - Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
methyl ethyl ketone	78-93-3	T, F
acetone	67-64-1	T, F
styrene	100-42-5	T, F
styrene	100-42-5	T, F
styrene	100-42-5	T, F

#### Legend

- F Flammability (NFPA®)
- T Toxicity (ACGIH®)



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals			
Name acc. to inventory	CAS No	Remarks	Type of the toxicity
styrene	100-42-5		cancer

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	3	material that can be ignited under almost all ambient temperature conditions
Health	0	material that, under emergency conditions, would offer no hazard beyond that of ordinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

### National regulations (Canada)

#### Domestic Substances List (DSL)

All ingredients are listed.

#### National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

Country	Inventory	Status
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
EU	REACH Reg.	not all ingredients are listed
TR	CICR	not all ingredients are listed

### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

## 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

## 16 Other information

### Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
"BC Regulation"	OHS Regulation: Section 5.48 (British Columbia)
ACGIH®	American Conference of Governmental Industrial Hygienists
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)



# Safety Data Sheet

acc. to Hazardous Products Regulations (HPR)

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

Abbr.	Descriptions of used abbreviations
DNEL	Derived No-Effect Level
ED	Endocrine disruptor
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
MoL	Ministry of Labor: Current Occupational Exposure Limits for Ontario Workplaces Required under Regulation 833
NFPA®	National Fire Protection Association (United States)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OHS Code	Occupational Health and Safety Code: Occupational exposure limits for chemical substances (Alberta)
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Regulation 833	R.R.O. 1990, Reg. 833: Control of exposure to biological or chemical agents (Ontario)
Regulation OHS	Regulation respecting occupational health and safety: Permissible exposure values for airborne contaminants (Quebec)
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit

## WELD-ON 771 YELLOW

Version number: 1.0

Date of compilation: 2024-02-16

Abbr.	Descriptions of used abbreviations
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TWA	Time-weighted average
UN RTDG	UN Recommendations on the Transport of Dangerous Good
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

Hazardous Products Regulations (HPR)

SOR/2022-272: Regulations Amending the Hazardous Products Regulations (GHS, Seventh Revised Edition)

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.

### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.