

# Maxi-Filtra®

Manufacturer: Studor®, Inc. Connection Size: 3" or 4"

#### General:

The MAXI-FILTRA is a two way vent, which filters air in both directions. It is designed for outdoor use only on septic tanks and lift stations. It is UV rated and comes with a re-placeable carbon filter to eliminate bad odors.

Buildings connected to the main sewer can also benefit from the use of the MAXI-FILTRA, but Studor technical department must be contacted so that installation feasibility can be determined. The MAXI-FILTRA, as part of the complete STUDOR System® elimi-nates sewer gases from entering buildings or polluting the surrounding areas. It can also be retro-fitted in an existing plumbing system provided that all design and installation criteria are met.

#### Location:

A. The MAXI-FILTRA is for outdoor use only

#### Installation:

- Install filter after drainage and waste system has been roughed in and tested.
- Install valves in accessible locations to allow for filter cartridge replacement.
- Connect valves to piping in accordance with manufacturer's instructions.
- Do not install valves on chemical waste systems or in supply and return air plenums. E. The MAXI-FILTRA can be installed vertically or horizontally
- F. The MAXI-FILTRA contains a replaceable carbon filter cartridge which can last up to 2 years.

### Features:

- A. UV inhibitor in resin compounds for exposure to sunlight
- B. Active Charcoal Filter replaceable cartridge

## Materials:

- A. ABS (acrylonitrile butadiene styrene)
- B. Active Charcoal Filter replaceable cartridge
- C. Rubber connector

Rated pressure (Pa)	Rated airflow (L/s) (Positive pressure)	Rated airflow (L/s) (Negative pressure)	
100	2.0	2.5	
250	3.4	4.3	
500	5.6	6.6	





PRODUCT	DESCRIPTION	MODEL	UNITS/CASE
20297	Maxi-Filtra® Two-Way Vent	20297	25
20700	Maxi-Filtra® Replacement Cartridge	20700	20